

Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/19/2015

Reviewed on 11/19/2015

Product Iden	ifier
Product Num Relevant ider Used for calibr Product Desc Calibration gas	tified uses of the substance or mixture and uses advised against: ation of gas measuring devices. Not suitable for human consumption.
Details of the Manufacturer Gasco Affiliate 320 Scarlett B Oldsmar, FI 34	s, LLC vd.
FAX NUMBER E-MAIL: info@ <i>Emergency te</i> Inside the US:	NUMBER: (800) 910-0051 :: (866) 755-8920 :gascogas.com e <b>lephone number:</b> 1-800-424-9300 (CHEMTREC, 24 hours) S: 1-703-527-3887 (CHEMTREC, 24 hours)
	5. 1-703-327-3007 (CHEWITTEC, 24 HOUS)
	dentification
Hazard(s) I	
Hazard(s) I Classification	dentification
Hazard(s) I Classification	dentification of the substance or mixture:
Hazard(s) I Classification GHS Press. Gas	dentification of the substance or mixture: 04 Gas cylinder
Hazard(s) I Classification GHS Press. Gas	dentification of the substance or mixture: 04 Gas cylinder H280 Contains gas under pressure; may explode if heated.
Hazard(s) I Classification GHS Press. Gas	dentification of the substance or mixture: 04 Gas cylinder H280 Contains gas under pressure; may explode if heated. 08 Health hazard H360 May damage fertility or the unborn child.
Hazard(s) I Classification GHS Press. Gas Press. Gas GHS Repr. 1A	dentification of the substance or mixture: 04 Gas cylinder H280 Contains gas under pressure; may explode if heated. 08 Health hazard H360 May damage fertility or the unborn child.
Hazard(s) I Classification GHS Press. Gas Press. Gas Repr. 1A GHS	dentification of the substance or mixture: 04 Gas cylinder H280 Contains gas under pressure; may explode if heated. 08 Health hazard H360 May damage fertility or the unborn child. 07 H332 Harmful if inhaled.

GHS04 GHS07 GHS08

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/19/2015

Reviewed on 11/19/2015

#### Trade name: Precision Calibration Gas Mixture

- · Signal word: Danger
- · Hazard-determining components of labeling:
- Carbon Monoxide
- Hazard statements:

Contains gas under pressure; may explode if heated.

Harmful if inhaled.

May damage fertility or the unborn child.

May displace oxygen and cause rapid suffocation.

#### Precautionary statements:

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

Store locked up.

Protect from sunlight. Store in a well-ventilated place.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Unknown acute toxicity:

100 % of the mixture consists of component(s) of unknown toxicity.

- · Classification system:
- · NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)

HEALTHIFIRE1Fire = 1REACTIVITYReactivity = 0

· Hazard(s) not otherwise classified (HNOC): None known

3 Composition/Information on Ingredients

· Chemical characterization: Mixtures

· Description: Mixture of substances listed below with non-hazardous additions.

 
 • Dangerous Components:

 CAS: 7727-37-9 RTECS: QW 970000
 Nitrogen
 75.3901 - 91.799%

 ◇ Press. Gas, H280; Simple Asphyxiant
 Oxygen
 8 - 21%

 CAS: 7782-44-7
 Oxygen
 8 - 21%

 ◇ Oxid. Gas 1, H270; ◇ Press. Gas, H280
 0.1 - 3.0%

 CAS: 74-82-8 RTECS: PA 1490000
 Methane
 0.1 - 3.0%

(Contd. on page 3)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/19/2015

Reviewed on 11/19/2015

#### Trade name: Precision Calibration Gas Mixture

CAS: 630-08-0 RTECS: FG 3500000	Carbon Monoxide line Flam. Gas 1, H220; line Acute Tox. 3, H331; line Repr. 1A, H360;	0.0005 - 0.51%
	STOT RE 1, H372; Press. Gas, H280	
CAS: 7783-06-4	Hydrogen Sulfide	0.0005 - 0.0999%
	♦ Flam. Gas 1, H220; ♦ Acute Tox. 2, H330; ♦ Aquatic Acute 1 H400; Press. Gas, H280	3

# 4 First-Aid Measures

### · Description of first aid measures:

#### After inhalation:

Generally the product does not irritate with inhalation.

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

#### • After skin contact:

Generally the product does not irritate the skin.

In cases of contact with liquified material, frostbite may occur. Immerse frostbite in cool-warm water and seek medical attention.

#### • After eye contact:

Not anticipated under normal use.

If irritation occurs thoroughly wash the exposed area and discontinue use. Seek medical attention if any adverse effect occurs.

- · After swallowing: Not a normal route of entry.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed:
- No further relevant information available.

### 5 Fire-Fighting Measures

#### • Extinguishing media:

• Suitable extinguishing agents:

Use fire fighting measures that suit the environment.

Use water spray to cool fire-exposed containers.

#### Special hazards arising from the substance or mixture:

Closed containers may explode when exposed to extreme heat.

If incinerated, product will release the following toxic fumes: Oxides of Carbon, Nitrogen (NOx) and Sulfur.

#### • Advice for firefighters:

This gas mixture is not flammable; however, containers, when involved in fire, may rupture or burst in the heat of the fire. Firefighters should be aware of the presence of Hydrogen Sulfide in this gas mixture, which can cause significant health effects.

#### Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

#### 6 Accidental Release Measures

• Personal precautions, protective equipment and emergency procedures:

In a confined area, NIOSH approved respiratory protection may be required. Treat any fumes as toxic.

- Environmental precautions: Inform authorities in case of gas release.
- Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/19/2015

*Reviewed on 11/19/2015* 

#### Trade name: Precision Calibration Gas Mixture

Ensure adequate ventilation. Dispose of the collected material according to regulations. • **Reference to other sections:** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and Storage

#### · Handling

#### Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Be aware of any signs of dizziness or fatigue; exposures to fatal concentrations of this gas mixture could occur without any significant warning symptoms due to the potential for oxygen deficiency (simple asphyxiation). Do not attempt to adjust, repain or in any other way modify the cylinders containing this gas mixture. If there is a malfunction or another type of operational problem, contact nearest distributor immediately.

#### Information about protection against explosions and fires:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Keep protective respiratory device available.

Do not cut, grind or weld on container that contains or contained product.

Do not spray on a naked flame or any incandescent material.

#### Conditions for safe storage, including any incompatibilities:

Store away from strong oxidizing agents, strong bases, phosphorous, organic materials and powdered metals. *Storage* 

#### • Requirements to be met by storerooms and receptacles:

Store in a cool location.

Cyliners should be firmly secured to prevent falling or being knocked over. Cylinders must be protected from the environment, and preferably kept at room temperature. Cylinders should be stored in dry, well-ventilated areas, away from sources of heat, ignition, and direct sunlight. Protect cylinders against physical damage. Full and empty cylinders should be segregated. Use a "first-in, first-out" inventory system to prevent full containers freom being stored for long periods of time.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s): No further relevant information available.

8 Exposure Controls/Personal Protection

• Additional information about design of technical systems: No further data; see section 7.

#### · Control parameters:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

<ul> <li>Components with occupational exposure limits:</li> </ul>	
7727-37-9 Nitrogen	
TLV withdrawn TLV, see App. F; simple asphyxiant	
74-82-8 Methane	
TLV refer to Appendix F, 1000ppm	
	(Contd. on page 5)

Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/19/2015

Reviewed on 11/19/2015

Trade name: Precision Calibration Gas Mixture

<u> </u>		
	08-0 Carbon Monoxide	
	Long-term value: 55 mg/m <sup>3</sup> , 50 pp	
REL	Long-term value: 40 mg/m <sup>3</sup> , 35 pp Ceiling limit value: 229 mg/m <sup>3</sup> , 200	
TLV	Long-term value: 29 mg/m³, 25 pp BEI	m
7783	-06-4 Hydrogen Sulfide	
PEL	Ceiling limit value: 20; 50* ppm	
	*10-min peak; once per 8-hr shift	
REL	Ceiling limit value: 15* mg/m³, 10* *10-min	
TLV	Short-term value: 7 mg/m <sup>3</sup> , 5 ppm Long-term value: 1.4 mg/m <sup>3</sup> , 1 ppn	
· Ingre	edients with biological limit value	PS:
630-	08-0 Carbon Monoxide	
BEI	3.5 % of hemoglobin	
	blood	
	end of shift Carboxyhemoglobin (background, r	nonspecific)
	20 ppm	
	end-exhaled air	
	end of shift Carbon monoxide (background, no	nenecific)
		vere valid during the creation of this SDS were used as basis.
<ul> <li>Pers</li> <li>Gend Keep Imme</li> <li>Wasi Store</li> <li>Brea Not r</li> <li>In ca use r</li> <li>Prote</li> </ul>	n hands before breaks and at the en- e protective clothing separately. thing equipment: necessary if room is well-ventilated. se of brief exposure or low pollution respiratory protective device that is ection of hands: Not required. protection: Not necessary under n	and feed. aminated clothing and wash before reuse. nd of work. n use respiratory filter device. In case of intensive or longer exposure, independent of circulating air.
9 Phy	sical and Chemical Propert	ies and a second se
· Gene · Appe Fo Co · Odo	mation on basic physical and ch eral Information earance: rm: lor: r: r: r threshold:	Gaseous Clear, colorless Mild Not determined.
· pH-v	alue:	Acidic
<i>VV</i>	,	(Contd. on page 6)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/19/2015

Trade name: Precision Calibration Gas Mixture

<ul> <li>Change in condition</li> <li>Melting point/Melting range:</li> <li>Boiling point/Boiling range:</li> </ul>	Not determined. -195 °C (-319 °F)
· Flash point:	None
· Flammability (solid, gaseous):	Not determined.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not self-igniting.
• Danger of explosion:	Not determined.
• Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapor pressure:	Not determined.
<ul> <li>Density @ 20 °C (68 °F):</li> <li>Relative density:</li> <li>Vapor density:</li> <li>Evaporation rate:</li> </ul>	0.023 g/cm³ (0.192 lbs/gal) Not determined. Not determined. Not applicable.
<ul> <li>Solubility in / Miscibility with: Water:</li> </ul>	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	r): Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
<ul> <li>Solvent content:</li> <li>Organic solvents:</li> <li>Other information:</li> </ul>	0.0 % No further relevant information available.
10 Stability and Reactivity	
<b>Beactivity</b> Stable under normal condi	liana

· *Reactivity:* Stable under normal conditions.

- · Chemical stability: Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: Heat, flame and ignition sources.
- · Incompatible materials:
- Strong oxidizing agents, strong bases, phosphorous, organic materials and powdered metals.
- Hazardous decomposition products: Oxides of Carbon, Nitrogen (NOx) and Sulfur.

#### 1 Toxicological Information

- · Information on toxicological effects:
- Acute toxicity:

#### · LD/LC50 values that are relevant for classification:

### 630-08-0 Carbon Monoxide

Inhalative LC50/4 h 7520 mg/l (rat)

(Contd. on page 7)

Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/19/2015

Reviewed on 11/19/2015

Trade name: Precision Calibration Gas Mixture

		• •
	Hydrogen Sulf	
Inhalative	LC50/4 h	634 mg/l (mouse)
		444 mg/l (rat)
		0.016 mg/l (Pimephales)
74-82-8 M		
Inhalative	LC50/4 h	217 mg/l (mouse)
<ul> <li>On the sk</li> <li>On the ey</li> <li>Additiona</li> <li>The prod</li> <li>preparatio</li> <li>Carcinoge</li> <li>IARC (Integration of the composition of the composit</li></ul>	ns: enic categories ernational Ager Carcinogenic to - Probably carci - Possibly carcir Not classifiable	ffect. <i>information:</i> following dangers according to internally approved calculation methods for :: icy for Research on Cancer):
	e ingredients ar	
•	onal Toxicolog	
None of th	e ingredients ar	e listed.
· OSHA-Ca	(Occupational	Safety & Health Administration):
None of th	e ingredients ar	e listed.
12 Ecologi	cal Informati	on
Aquatic to Persisten Bioaccun Mobility in Additiona General n Results o PBT: Not vPvB: Not	oxicity: No furth ce and degrada in environment nulative potenti n soil: No furthe el ecological inf potes: Generally f PBT and vPvb applicable. t applicable.	al: No further relevant information available. r relevant information available. formation: not hazardous for water.
13 Disposa	l Considerat	ions

# · Waste treatment methods:

• Recommendation:

Release all residual gas pressure in a well ventilated area. Verify the cylinder is completely empty (0 PSIG). Remove or cover any hazard labels. Return empty supplier for recycling.

NOTE: Check with the local waste authority before placing any gas cylinder into a waste container for pickup. GASCO encourages the consumer to return all cylinders.

· Waste disposal key: The U.S. EPA has not published waste numbers for this product's components.

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/19/2015

Trade name: Precision Calibration Gas Mixture

Reviewed on 11/19/2015

- · Uncleaned packagings:
- · Recommendation: Return cylinder and unused product to supplier.

4 Transport Information · UN-Number: · DOT, ADR, IMDG, IATA UN1956 • UN proper shipping name: DOT Compressed gas, n.o.s. · ADR UN1956 Compressed gas, n.o.s. · IMDG, IATA COMPRESSED GAS, N.O.S. Transport hazard class(es): · DOT 2.2 · Class: · Label: 2.2 · ADR 2.2 1A · Class: · Label: 2.2 · IMDG, IATA · Class: 2.2 · Label: 2.2 · Packing group: • Environmental hazards: Not applicable. - Special precautions for user: Not applicable. · Danger code (Kemler): 20 · EMS Number: F-C,S-V · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable. • Transport/Additional information: · DOT · Quantity limitations: On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg · ADR • Excepted quantities (EQ): Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml (Contd. on page 9)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/19/2015

Reviewed on 11/19/2015

Trade name: Precision Calibration Gas Mixture

· UN "Model Regulation":

UN1956, Compressed gas, n.o.s., 2.2

- 5 Regulatory Information
- Safety, health and environmental regulations/legislation specific for the substance or mixture: • SARA (Superfund Amendments and Reauthorization):
- Section 355 (extremely hazardous substances):
- 7783-06-4 Hydrogen Sulfide
- · Section 313 (Specific toxic chemical listings):
- 7783-06-4 Hydrogen Sulfide
- TSCA (Toxic Substances Control Act):
- All ingredients are listed.
- · California Proposition 65:
- · Chemicals known to cause cancer:
- None of the ingredients are listed.
- Chemicals known to cause reproductive toxicity for females:
- None of the ingredients are listed.
- · Chemicals known to cause reproductive toxicity for males:
- None of the ingredients are listed.
- · Chemicals known to cause developmental toxicity:
- 630-08-0 Carbon Monoxide
- · Carcinogenic categories:
- · EPA (Environmental Protection Agency):
- 7783-06-4 Hydrogen Sulfide
- TLV (Threshold Limit Value established by ACGIH):
- None of the ingredients are listed.
- NIOSH-Ca (National Institute for Occupational Safety and Health):
- None of the ingredients are listed.
- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms:



- · Signal word: Danger
- *Hazard-determining components of labeling:* Carbon Monoxide
- Hazard statements:

Contains gas under pressure; may explode if heated. Harmful if inhaled.

Mariniul II Innaleu.

May damage fertility or the unborn child. May displace oxygen and cause rapid suffocation. I

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/19/2015

Reviewed on 11/19/2015

#### Trade name: Precision Calibration Gas Mixture

#### · Precautionary statements:

Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF exposed or concerned: Get medical advice/attention. Store locked up. Protect from sunlight. Store in a well-ventilated place. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

#### State Right to Know:

Olute Hight to Khow.		
CAS: 7727-37-9	Nitrogen	75.3901 - 91.799%
RTECS: QW 9700000	Press. Gas, H280; Simple Asphyxiant	
CAS: 7782-44-7	Oxygen	8 - 21%
	🚸 Oxid. Gas 1, H270; 🔶 Press. Gas, H280	
CAS: 74-82-8	Methane	0.1 - 3.0%
RTECS: PA 1490000	🚸 Flam. Gas 1, H220; Press. Gas, H280	
CAS: 630-08-0	Carbon Monoxide	0.0005 - 0.51%
RTECS: FG 3500000	Flam. Gas 1, H220;  Acute Tox. 3, H331;  Repr. 1A, H360 STOT RE 1, H372; Press. Gas, H280	•
CAS: 7783-06-4	Hydrogen Sulfide	0.0005 - 0.0999%
	Flam. Gas 1, H220; H400; Press. Gas, H280	,
All ingredients are liste	d.	

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other Information

#### · Relevant phrases:

Gasco Affiliates, LLC, makes no express or implied warranties, guarantees or representations regarding the product or the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Gasco Affiliates, LLC shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use or reliance upon the information herein.

· Date of preparation / last revision: 11/19/2015 / -

Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/19/2015

Reviewed on 11/19/2015

#### Trade name: Precision Calibration Gas Mixture

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Gas 1: Flammable gases, Hazard Category 1 Oxid. Gas 1: Oxidising Gases, Hazard Category 1 Press. Gas: Gases under pressure: Compressed gas Acute Tox. 2: Acute toxicity, Hazard Category 2 Acute Tox. 3: Acute toxicity, Hazard Category 4 Repr. 1A: Reproductive toxicity, Hazard Category 1A STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1 \* **Data compared to the previous version altered.** SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106